

## JUMPER CABLE / PATCH CORD (ST)

### Specifications

Contact Ascentta with your custom specification needs.

Parameter		Unit	Value
Insertion Loss (23°C, All SOP)	Max	dB	0.3
Return Loss	Min	dB	40
Exchange	Max	dB	0.2
Repeatability	Max	dB	0.1
Durability	Min	Cycles	1000
Optical Power Handling	Max	mW	300
Operating Temperature		°C	-20 to +85
Storage Temperature		°C	-40 to +85

\* SOP=State Of Polarization

### Ordering Information

Contact Ascentta with your custom configuration needs.

JP	Fiber	Connector-1	Connector-2	Cable Type	Fiber Length
JP	S=SMF-28	FC=FC/PC	FC=FC/PC	B=250um	10=1.0m
	F1=1060 Flexcore	FA=FC/APC	FA=FC/APC	L=900um	20=2.0m
	H1=Hi-1060	LC=LC/PC	LC=LC/PC	W=2mm	30=3.0m
		LA=LC/APC	LA=LC/APC	H=3mm	35=3.5m
	X=Others	MC=MU/PC	MC=MU/PC		
		MA=MU/APC	MA=MU/APC	X=Others	X=Others
		SC=SC/PC	SC=SC/PC		
		SA=SC/APC	SA=SC/APC		
		ST=ST/PC	ST=ST/PC		
		MTRJ=MTRJ	MTRJ=MTRJ		
	D4=D4	D4=D4			
	X=Others	X=Others			

Contact Ascentta for all your custom design needs.