

FC JUMPER CABLE

Specifications

Parameter	Unit	PC	APC	Multi-mode
Insertion Loss	dB	≤0.2	≤0.2	≤0.3
Return Loss	dB	>40	>60	/
Exchange	dB		≤0.2	
Repeatability	dB		≤0.2	
Service Life	Time		>1000	
Tensile Strength	kg		>10	
Temperature Range	°C		-40 to +85	

Ordering Information

JP	Fiber	Connector-1	Connector-2	Cable Type	Fiber Length
JP	S=SMF-28	FC=FC/PC	FC=FC/PC	B=250um	10=1.0m
	M5=50/125 Multimode	SC=SC/PC	SC=SC/PC	L=900um	20=2.0m
	M6=62.5/125 Multimode	SU=SC/UPC	SU=SC/UPC	W=2mm	30=3.0m
		FA=FC/APC	FA=FC/APC	H=3mm	35=3.5m
	XX=Others	SA=SC/APC	SA=SC/APC		
		ST=ST/PC	ST=ST/PC	X=Others	XX=Others
		LC=LC/PC	LC=LC/PC		
		MC=MU/PC	MC=MU/PC		
		MA=MU/APC	MA=MU/APC		
		MTRJ=MTRJ	MTRJ=MTRJ		
	D4=D4	D4=D4			
	XX=Others	XX=Others			

SC JUMPER CABLE

Specifications

Parameter	Unit	PC	APC	Multi-mode
Insertion Loss	dB	≤0.2	≤0.2	≤0.2
Return Loss	dB	>40	>60	/
Exchange	dB		≤0.2	
Repeatability	dB		≤0.2	
Service Life	Time		>1000	
Tensile Strength	kg		>10	
Temperature Range	°C		-40 to +85	

Ordering Information

JP	Fiber	Connector-1	Connector-2	Cable Type	Fiber Length
JP	S=SMF-28	FC=FC/PC	FC=FC/PC	B=250um	10=1.0m
	M5=50/125 Multimode	SC=SC/PC	SC=SC/PC	L=900um	20=2.0m
	M6=62.5/125 Multimode	SU=SC/UPC	SU=SC/UPC	W=2mm	30=3.0m
		FA=FC/APC	FA=FC/APC	H=3mm	35=3.5m
	XX=Others	SA=SC/APC	SA=SC/APC		
		ST=ST/PC	ST=ST/PC	X=Others	XX=Others
		LC=LC/PC	LC=LC/PC		
		MC=MU/PC	MC=MU/PC		
		MA=MU/APC	MA=MU/APC		
		MTRJ=MTRJ	MTRJ=MTRJ		
	D4=D4	D4=D4			
	XX=Others	XX=Others			

ST JUMPER CABLE

Specifications

Parameter	Unit	Single Mode	Multi-mode
Insertion Loss	dB	≤0.3	≤0.2
Return Loss	dB	>40	/
Exchange	dB		≤0.2
Repeatability	dB		≤0.1
Service Life	Time		>1000
Tensile Strength	kg		>10
Temperature Range	°C		-40 to +85

Ordering Information

JP	Fiber	Connector-1	Connector-2	Cable Type	Fiber Length	
JP	S=SMF-28	FC=FC/PC	FC=FC/PC	B=250um	10=1.0m	
	M5=50/125 Multimode	SC=SC/PC	SC=SC/PC	L=900um	20=2.0m	
	M6=62.5/125 Multimode	SU=SC/UPC	SU=SC/UPC	W=2mm	30=3.0m	
	XX=Others	FA=FC/APC	FA=FC/APC	FA=FC/APC	H=3mm	35=3.5m
		SA=SC/APC	SA=SC/APC	SA=SC/APC	X=Others	XX=Others
		ST=ST/PC	ST=ST/PC	ST=ST/PC		
		LC=LC/PC	LC=LC/PC	LC=LC/PC		
		MC=MU/PC	MC=MU/PC	MC=MU/PC		
		MA=MU/APC	MA=MU/APC	MA=MU/APC		
		MTRJ=MTRJ	MTRJ=MTRJ	MTRJ=MTRJ		
	D4=D4	D4=D4	D4=D4			
XX=Others	XX=Others	XX=Others				

LC JUMPER CABLE

Specifications

Parameter	Unit	PC	APC	Multi-mode
Insertion Loss	dB	≤0.2	≤0.3	≤0.3
Return Loss	dB	>40	>60	/
Exchange	dB		≤0.3	
Repeatability	dB		≤0.2	
Service Life	Time		>1000	
Tensile Strength	kg		>10	
Temperature Range	°C		-40 to +85	

Ordering Information

JP	Fiber	Connector-1	Connector-2	Cable Type	Fiber Length	
JP	S=SMF-28	FC=FC/PC	FC=FC/PC	B=250um	10=1.0m	
	M5=50/125 Multimode	SC=SC/PC	SC=SC/PC	L=900um	20=2.0m	
	M6=62.5/125 Multimode	SU=SC/UPC	SU=SC/UPC	W=2mm	30=3.0m	
	XX=Others	FA=FC/APC	FA=FC/APC	FA=FC/APC	H=3mm	35=3.5m
		SA=SC/APC	SA=SC/APC	SA=SC/APC	X=Others	XX=Others
		ST=ST/PC	ST=ST/PC	ST=ST/PC		
		LC=LC/PC	LC=LC/PC	LC=LC/PC		
		MC=MU/PC	MC=MU/PC	MC=MU/PC		
		MA=MU/APC	MA=MU/APC	MA=MU/APC		
	MTRJ=MTRJ	MTRJ=MTRJ	MTRJ=MTRJ			
D4=D4	D4=D4	D4=D4				
XX=Others	XX=Others	XX=Others				

MU JUMPER CABLE

Specifications

Parameter	Unit	PC	APC	Multi-mode
Insertion Loss	dB	≤0.2	≤0.2	≤0.3
Return Loss	dB	>50	>60	/
Exchange	dB		≤0.2	
Repeatability	dB		≤0.2	
Service Life	Time		>1000	
Tensile Strength	kg		>10	
Temperature Range	°C		-40 to +85	

Ordering Information

JP	Fiber	Connector-1	Connector-2	Cable Type	Fiber Length	
JP	S=SMF-28	FC=FC/PC	FC=FC/PC	B=250um	10=1.0m	
	M5=50/125 Multimode	SC=SC/PC	SC=SC/PC	L=900um	20=2.0m	
	M6=62.5/125 Multimode	SU=SC/UPC	SU=SC/UPC	W=2mm	30=3.0m	
	XX=Others	FA=FC/APC	FA=FC/APC	FA=FC/APC	H=3mm	35=3.5m
		SA=SC/APC	SA=SC/APC	SA=SC/APC	X=Others	XX=Others
		ST=ST/PC	ST=ST/PC	ST=ST/PC		
		LC=LC/PC	LC=LC/PC	LC=LC/PC		
		MC=MU/PC	MC=MU/PC	MC=MU/PC		
		MA=MU/APC	MA=MU/APC	MA=MU/APC		
	MTRJ=MTRJ	MTRJ=MTRJ	MTRJ=MTRJ			
D4=D4	D4=D4	D4=D4				
XX=Others	XX=Others	XX=Others				

D4 JUMPER CABLE

Specifications

Parameter	Unit	Single Mode	Multi-mode
Insertion Loss	dB	≤0.3	≤0.3
Return Loss	dB	>50	/
Exchange	dB		≤0.2
Repeatability	dB		≤0.2
Service Life	Time		>1000
Tensile Strength	kg		>10
Temperature Range	°C		-40 to +85

Ordering Information

JP	Fiber	Connector-1	Connector-2	Cable Type	Fiber Length	
JP	S=SMF-28	FC=FC/PC	FC=FC/PC	B=250um	10=1.0m	
	M5=50/125 Multimode	SC=SC/PC	SC=SC/PC	L=900um	20=2.0m	
	M6=62.5/125 Multimode	SU=SC/UPC	SU=SC/UPC	W=2mm	30=3.0m	
	XX=Others	FA=FC/APC	FA=FC/APC	FA=FC/APC	H=3mm	35=3.5m
		SA=SC/APC	SA=SC/APC	SA=SC/APC	X=Others	XX=Others
		ST=ST/PC	ST=ST/PC	ST=ST/PC		
		LC=LC/PC	LC=LC/PC	LC=LC/PC		
		MC=MU/PC	MC=MU/PC	MC=MU/PC		
		MA=MU/APC	MA=MU/APC	MA=MU/APC		
		MTRJ=MTRJ	MTRJ=MTRJ	MTRJ=MTRJ		
	D4=D4	D4=D4	D4=D4			
XX=Others	XX=Others	XX=Others				

MTRJ JUMPER CABLE

Specifications

Parameter	Unit	Single Mode	Multi-mode
Insertion Loss	dB	≤0.5	≤0.5
Return Loss	dB	>35	/
Exchange	dB		≤0.3
Repeatability	dB		≤0.3
Service Life	Time		>1000
Tensile Strength	kg		>10
Temperature Range	°C		-40 to +85

Ordering Information

JP	Fiber	Connector-1	Connector-2	Cable Type	Fiber Length
JP	S=SMF-28	FC=FC/PC	FC=FC/PC	B=250um	10=1.0m
	M5=50/125 Multimode	SC=SC/PC	SC=SC/PC	L=900um	20=2.0m
	M6=62.5/125 Multimode	SU=SC/UPC	SU=SC/UPC	W=2mm	30=3.0m
		FA=FC/APC	FA=FC/APC	H=3mm	35=3.5m
	XX=Others	SA=SC/APC	SA=SC/APC		
		ST=ST/PC	ST=ST/PC	X=Others	XX=Others
		LC=LC/PC	LC=LC/PC		
		MC=MU/PC	MC=MU/PC		
		MA=MU/APC	MA=MU/APC		
		MTRJ=MTRJ	MTRJ=MTRJ		
	D4=D4	D4=D4			
	XX=Others	XX=Others			