

## D4 JUMPER CABLE

### Specifications

Parameter	Unit	Single Mode	Multi-mode
Insertion Loss	dB	≤0.3	≤0.3
Return Loss	dB	>50	/
Exchange	dB	≤0.2	
Repeatability	dB	≤0.2	
Service Life	Time	>1000	
Tensile Strength	kg	>10	
Temperature Range	°C	-40 to +85	

### Ordering Information

JP	Fiber	Connector-1	Connector-2	Cable Type	Fiber Length	
JP	S=SMF-28	FC=FC/PC	FC=FC/PC	B=250um	10=1.0m	
	M5=50/125 Multimode	SC=SC/PC	SC=SC/PC	L=900um	20=2.0m	
	M6=62.5/125 Multimode	SU=SC/UPC	SU=SC/UPC	W=2mm	30=3.0m	
	XX=Others	FA=FC/APC	FA=FC/APC	FA=FC/APC	H=3mm	35=3.5m
		SA=SC/APC	SA=SC/APC	SA=SC/APC	X=Others	XX=Others
		ST=ST/PC	ST=ST/PC	ST=ST/PC		
		LC=LC/PC	LC=LC/PC	LC=LC/PC		
		MC=MU/PC	MC=MU/PC	MC=MU/PC		
		MA=MU/APC	MA=MU/APC	MA=MU/APC		
	MTRJ=MTRJ	MTRJ=MTRJ	MTRJ=MTRJ			
D4=D4	D4=D4	D4=D4				
XX=Others	XX=Others	XX=Others				