

MTRJ JUMPER CABLE

Specifications

Parameter	Unit	Single Mode	Multi-mode
Insertion Loss	dB	≤0.5	≤0.5
Return Loss	dB	>35	/
Exchange	dB		≤0.3
Repeatability	dB		≤0.3
Service Life	Time		>1000
Tensile Strength	kg		>10
Temperature Range	°C		-40 to +85

Ordering Information

JP	Fiber	Connector-1	Connector-2	Cable Type	Fiber Length
JP	S=SMF-28	FC=FC/PC	FC=FC/PC	B=250um	10=1.0m
	M5=50/125 Multimode	SC=SC/PC	SC=SC/PC	L=900um	20=2.0m
	M6=62.5/125 Multimode	SU=SC/UPC	SU=SC/UPC	W=2mm	30=3.0m
		FA=FC/APC	FA=FC/APC	H=3mm	35=3.5m
	XX=Others	SA=SC/APC	SA=SC/APC		
		ST=ST/PC	ST=ST/PC	X=Others	XX=Others
		LC=LC/PC	LC=LC/PC		
		MC=MU/PC	MC=MU/PC		
		MA=MU/APC	MA=MU/APC		
		MTRJ=MTRJ	MTRJ=MTRJ		
	D4=D4	D4=D4			
	XX=Others	XX=Others			