

MU JUMPER CABLE

Specifications

| Parameter | Unit | PC | APC | Multi-mode |
|-------------------|------|------|------------|------------|
| Insertion Loss | dB | ≤0.2 | ≤0.2 | ≤0.3 |
| Return Loss | dB | >50 | >60 | / |
| Exchange | dB | | ≤0.2 | |
| Repeatability | dB | | ≤0.2 | |
| Service Life | Time | | >1000 | |
| Tensile Strength | kg | | >10 | |
| Temperature Range | °C | | -40 to +85 | |

Ordering Information

| JP | Fiber | Connector-1 | Connector-2 | Cable Type | Fiber Length |
|----|-----------------------|-------------|-------------|------------|--------------|
| JP | S=SMF-28 | FC=FC/PC | FC=FC/PC | B=250um | 10=1.0m |
| | M5=50/125 Multimode | SC=SC/PC | SC=SC/PC | L=900um | 20=2.0m |
| | M6=62.5/125 Multimode | SU=SC/UPC | SU=SC/UPC | W=2mm | 30=3.0m |
| | XX=Others | FA=FC/APC | FA=FC/APC | H=3mm | 35=3.5m |
| | | SA=SC/APC | SA=SC/APC | | |
| | | ST=ST/PC | ST=ST/PC | X=Others | XX=Others |
| | | LC=LC/PC | LC=LC/PC | | |
| | | MC=MU/PC | MC=MU/PC | | |
| | | MA=MU/APC | MA=MU/APC | | |
| | | MTRJ=MTRJ | MTRJ=MTRJ | | |
| | D4=D4 | D4=D4 | | | |
| | XX=Others | XX=Others | | | |