

## WDM FILTER (980/1550, or 1550/980nm)

### Specifications

Contact Ascentta with your custom specification needs.

Parameter		Unit	Value
Pass Channel	Wavelength	nm	1520~1600 (or 965~1000)
	Isolation (23°C, All SOP)	Min dB	30
	Insertion Loss (23°C, All SOP)	Max dB	1.0
Reflect Channel	Wavelength	nm	965~1000 (or 1520~1600)
	Isolation (23°C, All SOP)	Min dB	18
	Insertion Loss (23°C, All SOP)	Max dB	0.6
PDL		Max dB	0.15
PMD		Max ps	0.1
Return Loss		Min dB	50
Directivity		Min dB	60
Optical Power Handling		Max mW	300
Package Dimension		mm	φ5.5 x L35
Operating Temperature		°C	-20~+70
Storage Temperature		°C	-40~+85

\* The above specifications are for parts without connectors. Adding connectors can affect the IL, RL, & PDL.

\* SOP=State Of Polarization

### Ordering Information

Contact Ascentta with your custom configuration needs.

FWDM	Wavelength	Fiber Type	Fiber Length	Connector
FWDM	95=980pass/1550 reflect	B= SMF-28, 250um	10=1.0m	NE=None
	59=1550pass/980 reflect	L= SMF-28, 900um	15=1.5m	FA=FC/APC
	X=Others	X=Others	20=2.0m	FC=FC/PC
			30=3.0m	SA=SC/APC
			X=Others	SC=SC/PC
				ST=ST/PC
				LA=LC/APC
				LC=LC/PC
				X=Others

### Package Dimensions

