

## MINI-SIZE SINGLE-MODE COUPLER: WIDE-BAND (1310, 1550nm)

### Specifications

Contact Ascentta with your custom specification needs.

Parameter		Unit	Value
Wavelength		nm	1310 or 1550
Bandwidth		nm	±40
Excess Loss		Typ.	dB
Insertion Loss (23°C, All SOP)	50/50	Max	dB
	40/60	Max	dB
	30/70	Max	dB
	20/80	Max	dB
	10/90	Max	dB
	5/95	Max	dB
	2/98	Max	dB
	1/99	Max	dB
PDL		Max	dB
Directivity		Min	dB
Optical Power Handling		Max	mW
Operating Temperature		°C	-40 to 85
Storage Temperature		°C	-40 to 85


\* The above specifications are for parts without connectors. Adding connectors can affect the IL, & PDL.  
\* SOP=State Of Polarization

### Packaging

Contact Ascentta with your custom configuration needs.

Parameter		250µm bare fiber
Configuration		1x2 or 2x2
Dimension	mm	Φ2.4 x L25 (0.15 PDL) Φ2.4 x L30 (0.15 PDL) Φ3.0 x L30 Φ3.0 x L35

### Package Diagram



Contact Ascentta for all your custom design needs.

**MINI-SIZE SINGLE-MODE COUPLER: WIDE-BAND**  
(1310, 1550nm)

**Ordering Information**

Contact Ascentta with your custom configuration needs.

CP	Type	Wavelength	Coupler Ratio	Port	Package	Fiber Type	Cable Type	Fiber Length	Connector
CP	W=Wide-Band	13=1310	50=50/50	12=1x2	G25=Φ2.4 x L25	S=SMF-28	B=250um	05=0.5m	NE=None
		15=1550	20=20/80	22=2x2	G30=Φ2.4 x L30	X= Others	L=900um	10=1.0m	FA=FC/APC
		X: Others	10=10/90	X= Others	A30=Φ3.0 x L30		W=2mm	15=1.5m	FC=FC/PC
			05=05/95		A35=Φ3.0 x L35		H=3mm	20=2.0m	SA=SC/APC
			02=02/98					30=3.0m	SC=SC/PC
			01=01/99		X=Others			X=Others	ST=ST/PC
			X=Others						LA=LC/APC
									LC=LC/PC
									X=Others

Contact Ascentta for all your custom design needs.